

1 Identification

· **Product identifier**

· **Trade name:** Virent BioForm PX® Para-Xylene

· **Article number:** BioForm PX®

· **CAS Number:**

106-42-3

· **EC number:**

203-396-5

· **Index number:**

601-022-00-9

· **Relevant identified uses of the substance or mixture and uses advised against**

No further relevant information available.

· **Application of the substance / the mixture**

This material is only to be used for research and development, under the direct supervision of a technically qualified person. The toxicological properties have not been thoroughly investigated.

· **Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**

Virent, Inc.

3571 Anderson Street

Madison, WI USA 53704

· **Information department:** Product safety department: dave_runnels@virent.com

· **Emergency telephone number:**

For Chemical Emergency, Spill, Leak, Fire, Exposure or Accident, Call CHEMTREC (Day or Night)

CHEMTREC: NORTH AMERICA: 800-424-9300

CHEMTREC: INTERNATIONAL: CALL 703-527-3887 (collect calls accepted)

2 Hazard(s) identification

· **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS08 Health hazard

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Acute Tox. 4 H312 Harmful in contact with skin.

Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H335 May cause respiratory irritation.

Eye Irrit. 2B H320 Causes eye irritation.

· **Label elements**

· **GHS label elements**

The substance is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

Trade name: Virent BioForm PX® Para-Xylene

(Contd. of page 1)

· **Hazard pictograms**



· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

p-xylene

· **Hazard statements**

- H226 *Flammable liquid and vapor.*
- H312+H332 *Harmful in contact with skin or if inhaled.*
- H315+H320 *Causes skin and eye irritation.*
- H335 *May cause respiratory irritation.*
- H304 *May be fatal if swallowed and enters airways.*

· **Precautionary statements**

- P210 *Keep away from heat/sparks/open flames/hot surfaces. - No smoking.*
- P241 *Use explosion-proof electrical/ventilating/lighting/equipment.*
- P261 *Avoid breathing dust/fume/gas/mist/vapors/spray*
- P280 *Wear protective gloves / eye protection / face protection.*
- P280 *Wear protective gloves.*
- P280 *Wear protective gloves / protective clothing.*
- P240 *Ground/bond container and receiving equipment.*
- P242 *Use only non-sparking tools.*
- P243 *Take precautionary measures against static discharge.*
- P264 *Wash thoroughly after handling.*
- P271 *Use only outdoors or in a well-ventilated area.*
- P301+P310 *If swallowed: Immediately call a poison center/doctor.*
- P303+P361+P353 *IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.*
- P305+P351+P338 *If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.*
- P321 *Specific treatment (see on this label).*
- P304+P340 *IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.*
- P312 *Call a poison center/doctor if you feel unwell.*
- P332+P313 *If skin irritation occurs: Get medical advice/attention.*
- P337+P313 *If eye irritation persists: Get medical advice/attention.*
- P331 *Do NOT induce vomiting.*
- P370+P378 *In case of fire: Use for extinction: CO2, powder or water spray.*
- P362+P364 *Take off contaminated clothing and wash it before reuse.*
- P405 *Store locked up.*
- P403+P233 *Store in a well-ventilated place. Keep container tightly closed.*
- P403+P235 *Store in a well-ventilated place. Keep cool.*
- P501 *Dispose of contents/container in accordance with local/regional/national/international regulations.*

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



(Contd. on page 3)

Trade name: Virent BioForm PX® Para-Xylene

(Contd. of page 2)

· **HMIS-ratings (scale 0 - 4)**

| | | |
|------------|---|----------------|
| HEALTH | 1 | Health = 1 |
| FIRE | 3 | Fire = 3 |
| REACTIVITY | 0 | Reactivity = 0 |

- **Hazards Not Otherwise Classified** None
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Substances**
- **CAS No. Description**
106-42-3 p-xylene
- **Identification number(s)**
- **EC number:** 203-396-5
- **Index number:** 601-022-00-9

· **Components:**

| | | | |
|----------|--------------|---|--------|
| 108-88-3 | toluene | <ul style="list-style-type: none"> Flam. Liq. 2, H225; Repr. 2, H361; STOT RE 2, H373; Asp. Tox. 1, H304; Skin Irrit. 2, H315; STOT SE 3, H336 | ≤ 2.5% |
| 100-41-4 | ethylbenzene | <ul style="list-style-type: none"> Flam. Liq. 2, H225; Carc. 2, H351; Acute Tox. 4, H332 | ≤ 2.5% |

4 First-aid measures

- **Description of first aid measures**
- **General information:**
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:**
Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.

(Contd. on page 4)

Trade name: Virent BioForm PX® Para-Xylene

(Contd. of page 3)

- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

106-42-3 p-xylene (50-100%)

| | |
|-----|---|
| PEL | Long-term value: 435 mg/m ³ , 100 ppm |
| REL | Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm |
| TLV | Short-term value: 651 mg/m ³ , 150 ppm Long-term value: 434 mg/m ³ , 100 ppm |
| BEI | |

(Contd. on page 5)

Trade name: Virent BioForm PX® Para-Xylene

(Contd. of page 4)

· **Ingredients with biological limit values:**

106-42-3 p-xylene (50-100%)

| | |
|-----|--|
| BEI | 1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids |
|-----|--|

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Avoid contact with the skin.
Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

| | |
|--------------------|-----------------|
| Form: | Fluid |
| Color: | Transparent |
| · Odor: | Characteristic |
| · Odour threshold: | Not determined. |

| | |
|-------------|-----------------|
| · pH-value: | Not determined. |
|-------------|-----------------|

(Contd. on page 6)

Trade name: Virent BioForm PX® Para-Xylene

(Contd. of page 5)

| | |
|---|--|
| · Change in condition | |
| Melting point/Melting range: | 13.3 °C (56 °F) |
| Boiling point/Boiling range: | 138.7 °C (282 °F) |
| · Flash point: | 25 °C (77 °F) |
| · Flammability (solid, gaseous): | Not applicable. |
| · Ignition temperature: | 525 °C (977 °F) |
| · Decomposition temperature: | Not determined. |
| · Auto igniting: | Not determined. |
| · Danger of explosion: | Product is not explosive. However, formation of explosive air/vapor mixtures are possible. |
| · Explosion limits: | |
| Lower: | 1.7 Vol % |
| Upper: | 7.6 Vol % |
| · Vapor pressure at 20 °C (68 °F): | 8.2 hPa (6 mm Hg) |
| · Density at 20 °C (68 °F): | 0.99767 g/cm ³ (8.326 lbs/gal) |
| · Relative density | Not determined. |
| · Vapour density | Not determined. |
| · Evaporation rate | Not determined. |
| · Solubility in / Miscibility with Water at 20 °C (68 °F): | 0.2 g/l |
| · Partition coefficient (n-octanol/water): | Not determined. |
| · Viscosity: | |
| Dynamic at 20 °C (68 °F): | 0.648 mPas |
| Kinematic: | Not determined. |
| · Solvent content: | |
| Organic solvents: | 99.5 % |
| | Not tested |
| VOC content: | 99.5 % |
| | 992.7 g/l / 8.28 lb/gl |
| · Other information | No further relevant information available. |

10 Stability and reactivity

- **Reactivity**
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

US

(Contd. on page 7)

Trade name: Virent BioForm PX® Para-Xylene

(Contd. of page 6)

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

106-42-3 p-xylene

| | | |
|------------|----------|------------------|
| Oral | LD50 | 5000 mg/kg (rat) |
| Dermal | LD50 | 1100 mg/kg (ATE) |
| Inhalative | LC50/4 h | 11 mg/l (ATE) |

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** No irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

| | | |
|----------|--------------|----|
| 106-42-3 | p-xylene | 3 |
| 108-38-3 | m-xylene | 3 |
| 108-88-3 | toluene | 3 |
| 100-41-4 | ethylbenzene | 2B |
| 95-47-6 | o-xylene | 3 |

- **NTP (National Toxicology Program)**

Substance is not listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

Substance is not listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
- Water hazard class 2 (Assessment by list): hazardous for water
- Do not allow product to reach ground water, water course or sewage system.
- Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

US

(Contd. on page 8)



Trade name: Virent BioForm PX® Para-Xylene

(Contd. of page 7)

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** *Disposal must be made according to official regulations.*

14 Transport information

| | |
|--|---|
| · UN-Number | |
| · DOT, ADR, IMDG, IATA | UN1307 |
| · UN proper shipping name | |
| · DOT | Xylenes |
| · ADR | 1307 Xylenes |
| · IMDG, IATA | XYLENES |
| · Transport hazard class(es) | |
| · DOT | |
| |  |
| · Class | 3 Flammable liquids |
| · Label | 3 |
| · ADR, IMDG, IATA | |
| |  |
| · Class | 3 Flammable liquids |
| · Label | 3 |
| · Packing group | |
| · DOT, ADR, IMDG, IATA | III |
| · Environmental hazards: | |
| · Marine pollutant: | No |
| · Special precautions for user | Warning: Flammable liquids |
| · Danger code (Kemler): | 30 |
| · EMS Number: | F-E,S-D |
| · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | Not applicable. |
| · Transport/Additional information: | |
| · DOT | |
| · Quantity limitations | On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L |

(Contd. on page 9)

Trade name: Virent BioForm PX® Para-Xylene

(Contd. of page 8)

- | | |
|--|--|
| · ADR · Excepted quantities (EQ) | Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml |
| · IMDG · Limited quantities (LQ) · Excepted quantities (EQ) | 5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml |
| · UN "Model Regulation": | UN1307, Xylenes, 3, III |

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

- **Section 355 (extremely hazardous substances):**

Substance is not listed.

- **Section 313 (Specific toxic chemical listings):**

Substance is listed.

- **TSCA (Toxic Substances Control Act):**

Substance is listed.

- **Proposition 65**

- **Chemicals known to cause cancer:**

100-41-4 ethylbenzene

- **Chemicals known to cause reproductive toxicity for females:**

108-88-3 toluene

- **Chemicals known to cause reproductive toxicity for males:**

Substance is not listed.

- **Chemicals known to cause developmental toxicity:**

108-88-3 toluene

- **Carcinogenicity categories**

- **EPA (Environmental Protection Agency)**

| | | |
|----------|--------------|----|
| 106-42-3 | p-xylene | I |
| 108-38-3 | m-xylene | I |
| 108-88-3 | toluene | II |
| 100-41-4 | ethylbenzene | D |
| 95-47-6 | o-xylene | I |

- **TLV (Threshold Limit Value established by ACGIH)**

| | | |
|----------|--------------|----|
| 106-42-3 | p-xylene | A4 |
| 108-38-3 | m-xylene | A4 |
| 108-88-3 | toluene | A4 |
| 100-41-4 | ethylbenzene | A3 |
| 95-47-6 | o-xylene | A4 |

(Contd. on page 10)

Trade name: Virent BioForm PX® Para-Xylene

(Contd. of page 9)

 · **NIOSH-Ca (National Institute for Occupational Safety and Health)**

Substance is not listed.

 · **GHS label elements**

The substance is classified and labeled according to the Globally Harmonized System (GHS).

 · **Hazard pictograms**


GHS02 GHS07 GHS08

 · **Signal word** *Danger*

 · **Hazard-determining components of labeling:**
p-xylene

 · **Hazard statements**

 H226 *Flammable liquid and vapor.*

 H312+H332 *Harmful in contact with skin or if inhaled.*

 H315+H320 *Causes skin and eye irritation.*

 H335 *May cause respiratory irritation.*

 H304 *May be fatal if swallowed and enters airways.*

 · **Precautionary statements**

 P210 *Keep away from heat/sparks/open flames/hot surfaces. - No smoking.*

 P241 *Use explosion-proof electrical/ventilating/lighting/equipment.*

 P261 *Avoid breathing dust/fume/gas/mist/vapors/spray*

 P280 *Wear protective gloves / eye protection / face protection.*

 P280 *Wear protective gloves.*

 P280 *Wear protective gloves / protective clothing.*

 P240 *Ground/bond container and receiving equipment.*

 P242 *Use only non-sparking tools.*

 P243 *Take precautionary measures against static discharge.*

 P264 *Wash thoroughly after handling.*

 P271 *Use only outdoors or in a well-ventilated area.*

 P301+P310 *If swallowed: Immediately call a poison center/doctor.*

 P303+P361+P353 *IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.*

 P305+P351+P338 *If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.*

 P321 *Specific treatment (see on this label).*

 P304+P340 *IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.*

 P312 *Call a poison center/doctor if you feel unwell.*

 P332+P313 *If skin irritation occurs: Get medical advice/attention.*

 P337+P313 *If eye irritation persists: Get medical advice/attention.*

 P331 *Do NOT induce vomiting.*

 P370+P378 *In case of fire: Use for extinction: CO2, powder or water spray.*

 P362+P364 *Take off contaminated clothing and wash it before reuse.*

 P405 *Store locked up.*

 P403+P233 *Store in a well-ventilated place. Keep container tightly closed.*

 P403+P235 *Store in a well-ventilated place. Keep cool.*

 P501 *Dispose of contents/container in accordance with local/regional/national/international regulations.*

(Contd. on page 11)



Safety Data Sheet

acc. to OSHA HCS

Printing date 05/06/2015

Reviewed on 05/06/2015

Trade name: Virent BioForm PX® Para-Xylene

(Contd. of page 10)

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Date of preparation / last revision** 05/06/2015 / -

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Flam. Liq. 3: Flammable liquids, Hazard Category 3

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2B: Serious eye damage/eye irritation, Hazard Category 2B

Carc. 2: Carcinogenicity, Hazard Category 2

Repr. 2: Reproductive toxicity, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2

Asp. Tox. 1: Aspiration hazard, Hazard Category 1

US